



ADP-390

Design	5-driver, 3-way surround / rear
Crossover	2nd-order electro-acoustic at 3.0 kHz, 2nd-order electro-acoustic at 250 Hz (bass drivers)
High-Frequency Driver	Two 25-mm (1 in) H-PTD™ domes, ferro-fluid cooled
Midrange Driver(s)	Two 115-mm (4-1/2 in) M-ICP™ cones, 25-mm (1 in) voice coils, ferro-fluid cooled, GRIP™ chassis
Bass Driver	190-mm (7-1/2 in) carbon-infused polypropylene cone, 38-mm (1-1/2 in) voice coil, die-cast heatsink chassis
Low Frequency Extension	70 Hz (DIN)
Frequency Response:	
On-Axis	±2 dB from 100 Hz - 20 kHz (reverberant soundfield)
30° Off-Axis	±
Sensitivity - Room / Anechoic	90 dB / 87 dB
Suitable Amplifier Power Range	15 - 175 watts
Maximum Input Power	120 watts
Impedance	Compatible with 8 ohms
Internal Volume	8.1 L / 0.28 cu ft
Height, Width, Depth	24.6 cm x 35.5 cm x 17.3 cm
	9-11/16 in x 14 in x 6-13/16 in
Weight (Unpacked)	5.9 kg / 13 lb each
Finishes	Black, White
Matching Speaker Stand	S-26, J-29