



**Paradigm**

THE ULTIMATE IN SOUND FOR MUSIC AND HOME THEATER™



## AMS-150R-30

Design	2-driver, 2-way in-ceiling / in-wall, drivers mounted at 30° relative to mounting surface, GRIP™ chassis / mounting bracket
Crossover	2nd-order electro-acoustic at 2.5 kHz
High-Frequency Driver	25-mm (1 in) S-PAL™ dome, die-cast heatsink chassis, ferro-fluid cooled
Bass/Midrange Driver(s)	210-mm (8 in) mineral-filled polypropylene cone, GRIP™ chassis
Low Frequency Extension	45 Hz (DIN)
Frequency Rresponse on axis	±2 db from 60 Hz - 22 kHz
Frequency Rresponse 30 off axis	±2 dB from 60 Hz - 16 kHz
Sensitivity-Room/Anechoic	91 dB / 87 dB
Suitable Amplifier Power Range	110 - 15 watts
Maximum Input Power	80 watts
Impedance	Compatible with 8 ohms
Height,Width or Diameter	29.6 cm / 11-5/8 in (Diameter)
Minimum Mounting Depth	14.3 cm /5-5/8 in
Cutout Dimensions Diameter	27
Minimum Internal Volume Required	20 L / 0.7 cu ft
Pre-Installation Brackets	PB-10R

Weight	5lb / 2.30kg
Finishes	White, paintable