



Paradigm

THE ULTIMATE IN SOUND FOR MUSIC AND HOME THEATER™



AMS-150RX

Design	2-driver, coaxially mounted high-frequency driver, 2-way in-ceiling / in-wall, GRIP™ chassis / mounting bracket, Xtreme Moisture Application™ version, stainless steel grilles
Crossover	2nd-order electro-acoustic at 2.5 kHz
High-Frequency Driver	25-mm (1 in) S-PAL™ dome, die-cast heatsink, ferro-fluid cooled
Bass/Midrange Driver(s)	210-mm (8 in) mineral-filled polypropylene cone, GRIP™ chassis
Low Frequency Extension	45 Hz (DIN)
Frequency Rresponse on axis	±2 dB from 60 Hz - 22 kHz
Frequency Rresponse 30 off axis	±2 dB from 60 Hz - 20 kHz
Sensitivity-Room/Anechoic	91 dB / 87 dB
Suitable Amplifier Power Range	15 - 110 watts
Maximum Input Power	80 watts
Impedance	Compatible with 8 ohms
Height,Width or Diameter	22.6 cm / 8-7/8 in (Diameter)
Minimum Mounting Depth	8.3 cm /3-1/4 in
Cutout Dimensions Diameter	20
Minimum Internal Volume Required	20 L / 0.7 cu ft

Weight	7.9lb / 3.60kg
Finishes	White, paintable