



Paradigm

THE ULTIMATE IN SOUND FOR MUSIC AND HOME THEATER™



AMS-350

Design	3-driver, 2-way in-ceiling / in-wall, die-cast chassis / mounting bracket
Crossover	2nd-order electro-acoustic at 1.8 kHz
High-Frequency Driver	25-mm (1 in) PTD™ dome with die-cast heatsink faceplate
Bass/Midrange Driver(s)	Two 210-mm (8-in) mineral-filled polypropylene cones, die-cast chassis
Low Frequency Extension	35 Hz (DIN)
Frequency Rresponse on axis	±2 dB from 55 Hz - 20 kHz
Frequency Rresponse 30 off axis	±2 dB from 55 Hz - 18 kHz
Sensitivity-Room/Anechoic	93 dB/ 89 dB
Suitable Amplifier Power Range	200 - 15 watts
Maximum Input Power	150 watts
Impedance	Compatible with 8 ohms
Height,Width or Diameter	51 cm x23.1 cm / 20-1/16 in x9-1/8 in (Height x Width)
Minimum Mounting Depth	7.6 cm /3 in
Cutout Dimensions	
Height x Width	19-1/8 in x 8-1/8 in (Height x Width)
Minimum Internal Volume Required	40 L / 1.4 cu ft
Weight	20lb / 9.10kg

Finishes

White, paintable