



**Paradigm**

THE ULTIMATE IN SOUND FOR MUSIC AND HOME THEATER™



## CC-390

Design	7-driver, 3-way center channel, MagneShield™††
Crossover	2nd-order electro-acoustic at 2.4 kHz, 2nd-order electro-acoustic at 250 Hz (bass drivers)
High-Frequency Driver	25-mm (1 in) H-PTD™ dome, ferro-fluid cooled
Midrange Driver(s)	Two 115-mm (4-1/2 in) M-ICP™ cones, 25-mm (1 in) voice coils, ferro-fluid cooled, GRIP™ chassis
Bass Driver	Four 165-mm (6-1/2 in) carbon-infused polypropylene cones, 25-mm (1 in) voice coils, die-cast heatsink chassis
Low Frequency Extension	43 Hz (DIN)
Frequency Response:	
On-Axis	±2 dB from 75 Hz - 20 kHz
30° Off-Axis	±2 dB from 75 Hz - 17 kHz
Sensitivity - Room / Anechoic	97 dB / 94 dB
Suitable Amplifier Power Range	15 - 200 watts
Maximum Input Power	150 watts
Impedance	Compatible with 8 ohms
Internal Volume	49.9 L / 1.76 cu ft
Height, Width, Depth	21.5 cm x 99 cm x 37.1 cm
	8-7/16 in x 39 in x 14-5/8 in
Weight (Unpacked)	27.7 kg / 61 lb each
Finishes	Wengé, Cherry, Rosenut, Black Ash
Paradigm® Stand (sold sep.)	Paradigm® J-18C