



Paradigm

THE ULTIMATE IN SOUND FOR MUSIC AND HOME THEATER™



CS-150

Design	2-driver, 2-way in-ceiling / in-wall, IRP™ chassis / mounting bracket
Crossover	2nd-order electro-acoustic at 2.5 kHz
High-Frequency Driver	19-mm (3/4 in) PTD™ dome
Bass/Midrange Driver(s)	140-mm (5-1/2 in) mineral-filled polypropylene cone
Low Frequency Extension	60 Hz (DIN)
Frequency Response on axis	±2 dB from 75 Hz - 20 kHz
Frequency Response 30 off axis	±2 dB from 75 Hz - 18 kHz
Sensitivity-Room/Anechoic	88 dB / 84 dB
Suitable Amplifier Power Range	80 - 15 watts
Maximum Input Power	50 watts
Impedance	Compatible with 8 ohms
Height,Width or Diameter	25 cm x18 cm / 9-13/16 in x7-1/16 in (Height x Width)
Minimum Mounting Depth	5.4 cm /2-1/8 in
Cutout Dimensions	
Height x Width	9-3/16 in x 6-1/16 in (Height x Width)
Minimum Internal Volume Required	6 L / 0.2 cu ft
Pre-Installation Brackets	PB-6x9; retrofit included
Weight	5lb / 2.30kg
Finishes	White, paintable