



**Paradigm**

THE ULTIMATE IN SOUND FOR MUSIC AND HOME THEATER™



## CS-60R

Design	2-driver, coaxially mounted high-frequency driver, 2-way in-ceiling / in-wall, IRP™ chassis / mounting bracket
Crossover	2nd-order electro-acoustic at 3.0 kHz
High-Frequency Driver	19-mm (3/4 in) PTD™ dome
Bass/Midrange Driver(s)	165-mm (6-1/2 in) mineral-filled polypropylene cone
Low Frequency Extension	55 Hz (DIN)
Frequency Rresponse on axis	±2 dB from 70 Hz - 20 kHz
Frequency Rresponse 30 off axis	±2 dB from 70 Hz - 18 kHz
Sensitivity-Room/Anechoic	89 dB / 85 dB
Suitable Amplifier Power Range	80 - 15 watts
Maximum Input Power	50 watts
Impedance	Compatible with 8 ohms
Height,Width or Diameter	22 cm / 8-11/16 in (Diameter)
Minimum Mounting Depth	6 cm /2-3/8 in
Cutout Dimensions Diameter	19.6
Minimum Internal Volume Required	12 L / 0.4 cu ft
Weight	7lb / 3.20kg
Finishes	White, paintable