



Paradigm

THE ULTIMATE IN SOUND FOR MUSIC AND HOME THEATER™



CS-60R-30

Design	2-driver, coaxially mounted high-frequency driver, 2-way in-ceiling / in-wall, drivers mounted at 30° relative to mounting surface, IRP™ chassis / mounting bracket
Crossover	2nd-order electro-acoustic at 3.0 kHz
High-Frequency Driver	25-mm (1 in) PTD™ dome
Bass/Midrange Driver(s)	165-mm (6-1/2 in) mineral-filled polypropylene cone
Low Frequency Extension	55 Hz (DIN)
Frequency Rresponse on axis	±2 dB from 70 Hz - 20 kHz
Frequency Rresponse 30 off axis	±2 dB from 70 Hz - 15 kHz
Sensitivity-Room/Anechoic	89 dB / 85 dB
Suitable Amplifier Power Range	80 - 15 watts
Maximum Input Power	50 watts
Impedance	Compatible with 8 ohms
Height,Width or Diameter	29 cm / 11-7/16 in (Diameter)
Minimum Mounting Depth	12 cm /4-3/4 in
Cutout Dimensions Diameter	26.6
Minimum Internal Volume Required	12 L / 0.4 cu ft
Pre-Installation Brackets	PB-10R; retrofit included
Weight	5.3lb / 2.40kg
Finishes	White, paintable