



CS-60SQ-SM

Design	Single speaker system with Stereo L/R inputs, 2 x 2-way in-ceiling / in-wall, coaxially mounted high-frequency drivers, 3-driver, IRP™ chassis / mounting bracket
Crossover	Two 2nd-order electro-acoustic at 3.0kHz
High-Frequency Driver	Two 19-mm (3/4 in) PTD™ domes
Bass/Midrange Driver(s)	Dual voice coil, 165-mm (6-1/2 in) mineral-filled polypropylene cone
Low Frequency Extension	52 Hz (DIN)
Frequency Rresponse on axis	±2 dB from 70 Hz - 20 kHz
Frequency Rresponse 30 off axis	±2 dB from 70 Hz - 15 kHz
Sensitivity-Room/Anechoic	89 dB / 85 dB
Suitable Amplifier Power Range	80 - 15 watts
Maximum Input Power	50 watts
Impedance	Compatible with 4 ohms Mono; 8 ohms / channel Stereo
Height,Width or Diameter	20 cm x20 cm / 7-7/8 in x7-7/8 in (Height x Width)
Minimum Mounting Depth	7.1 cm /2-13/16 in
Cutout Dimensions	
Height x Width	7-1/16 in x 7-1/16 in (Height x Width)
Minimum Internal Volume Required	12 L / 0.4 cu ft
Pre-Installation Brackets	PB-7x7; retrofit included

Weight	3.5lb / 1.60kg
Finishes	White, paintable