



**Paradigm**

THE ULTIMATE IN SOUND FOR MUSIC AND HOME THEATER™



### CS-LCR

Design	Left / Center / Right, 3-driver, 2-way in-wall, IRP™ chassis / mounting bracket
Crossover	2nd-order electro-acoustic at 2.5 kHz
High-Frequency Driver	19-mm (3/4 in) PTD™ dome, ferro-fluid cooled
Bass/Midrange Driver(s)	Two 140-mm (5-1/2 in) mineral-filled polypropylene cones
Low Frequency Extension	60 Hz (DIN)
Frequency Rresponse on axis	±2 dB from 75 Hz - 20 kHz
Frequency Rresponse 30 off axis	±2 dB from 75 Hz - 18 kHz
Sensitivity-Room/Anechoic	89 dB / 85 dB
Suitable Amplifier Power Range	15 - 100 watts
Maximum Input Power	70 watts
Impedance	Compatible with 8 ohms
Height,Width or Diameter	31.7 cm x23.1 cm / 12-1/2 in x9-1/8 in (Height x Width)
Minimum Mounting Depth	6.4 cm /2-1/2 in
Cutout Dimensions	
Height x Width	11-9/16 in x 8-1/8 in (Height x Width)
Minimum Internal Volume Required	12 L / 0.4 cu ft
Pre-Installation Brackets	PB-8X12
Weight	5.9lb / 2.70kg
Finishes	White, paintable