



### **PV-150**

Design	2-driver, 2-way in-wall / in-ceiling, IRP™ chassis / mounting bracket
Crossover	2nd-order electro-acoustic at 2.5 kHz
High-Frequency Driver	25-mm (1 in) silk dome
Bass/Midrange Driver(s)	140-mm (5-1/2 in) mineral-filled polypropylene cone
Low Frequency Extension	60 Hz (DIN)
Frequency Response on axis	±2 dB from 75 Hz - 20 kHz
Frequency Response 30 off axis	±2 dB from 75 Hz - 18 kHz
Sensitivity-Room/Anechoic	88 dB / 84 dB
Suitable Amplifier Power Range	70 - 15 watts
Maximum Input Power	40 watts
Impedance	Compatible with 8 ohms
Height,Width or Diameter	26.3 cm x18.6 cm / 10-3/8 in x7-5/16 in (Height x Width)
Minimum Mounting Depth	5.9 cm /2-5/16 in
Cutout Dimensions	
Height x Width	9-1/8 in x 6 in (Height x Width)
Minimum Internal Volume Required	6 L / 0.2 cu ft
External dimensions	23.2 cm x 15.2 cm (Height x Width)
Pre-Installation Brackets	PB-6x9; retrofit included
Weight	7.3lb / 3.30kg

Finishes

White, paintable