



Paradigm

THE ULTIMATE IN SOUND FOR MUSIC AND HOME THEATER™



PV-160

Design	2-driver, 2-way in-wall / in-ceiling, IRP™ chassis / mounting bracket
Crossover	2nd-order electro-acoustic at 2.5 kHz
High-Frequency Driver	25-mm (1 in) silk dome
Bass/Midrange Driver(s)	165-mm (6-1/2 in) mineral-filled polypropylene cone
Low Frequency Extension	55 Hz (DIN)
Frequency Response on axis	±2 dB from 70 Hz - 20 kHz
Frequency Response 30 off axis	±2 dB from 70 Hz - 18 kHz
Sensitivity-Room/Anechoic	89 dB / 85 dB
Suitable Amplifier Power Range	80 - 15 watts
Maximum Input Power	50 watts
Impedance	Compatible with 8 ohms
Height,Width or Diameter	28.5 cm x20.8 cm / 11-1/4 in x8-3/16 in (Height x Width)
Minimum Mounting Depth	6.5 cm /2-9/16 in
Cutout Dimensions	
Height x Width	9-15/16 in x 6-15/16 in (Height x Width)
Minimum Internal Volume Required	12 L / 0.4 cu ft
External dimensions	25.2 cm x 17.7 cm (Height x Width)
Pre-Installation Brackets	PB-7x10; retrofit included
Weight	9.7lb / 4.40kg

Finishes

White, paintable