



## Millenia™ 20 Trio

Design	9-driver, 3-channel (2-way center; 2-1/2-way Left and Right) acoustic suspension, on-wall / shelf-mounted, MagneShield™††
Crossover	2nd-order electro-acoustic at 2.0 kHz, 2nd-order electro-acoustic at 800 Hz (bass drivers on Left and Right channels)
High-Frequency Driver	Three 25-mm (1 in) S-PAL™ domes, die-cast chassis, ferro-fluid cooled
Bass / Midrange Driver(s)	Four 115-mm (4-1/2 in) MLP™ cones, 25-mm (1 in) dual-layer voice coils, HTD™ system die-cast heatsink chassis
Bass Driver	Two 115-mm (4-1/2 in) mineral-filled polypropylene cones, 25-mm (1 in) dual-layer voice coils, HTD™ system die-cast heatsink chassis
Low Frequency Extension	80 Hz (DIN)
Frequency Response:	
On-Axis	±2 dB from 120 Hz - 20 kHz
30° Off-Axis	±2 dB from 120 Hz - 18 kHz
Sensitivity - Room / Anechoic	90 dB / 87 dB
Suitable Amplifier Power Range	15 - 150 watts
Maximum Input Power	90 watts
Impedance	Compatible with 8 ohms

Internal Volume	7.7 L / 0.27 cu ft
Height, Width, Depth	13 cm x 105 cm x 12 cm
	5-1/8 in x 41-5/16 in x 4-3/4 in
Weight	8.2 kg / 18 lb each
Finishes	Polished Aluminum, Black Chrome