



## Millenia™ 300

Design	6-driver, 2-1/2-way bass reflex, floorstanding design, MagneShield™††
Crossover	2nd-order electro-acoustic at 1.0 kHz (bass drivers), 2nd-order electro-acoustic at 2.0 kHz
High-Frequency Driver	25-mm (1 in) S-PAL™ dome, die-cast chassis, ferro-fluid cooled
Bass / Midrange Driver(s)	Two 140-mm (5-1/2 in) MLP™ cones, 25-mm (1 in) dual-layer voice coils, HTD™ system die-cast heatsink chassis
Bass Driver	Three 140-mm (5-1/2 in) mineral-filled polypropylene cones, 38-mm (1-1/2 in) dual-layer voice coils, HTD™ system die-cast heatsink chassis
Low Frequency Extension	54 Hz (DIN)
Frequency Response:	
On-Axis	±2 dB from 87 Hz - 20 kHz
30° Off-Axis	±2 dB from 87 Hz - 18 kHz
Sensitivity - Room / Anechoic	94 dB / 91 dB
Suitable Amplifier Power Range	15 - 200 watts
Maximum Input Power	150 watts
Impedance	Compatible with 8 ohms
Internal Volume	16.8 L / 0.59 cu ft
Height, Width, Depth	133.3 cm x 15.1 cm x 17.5 cm

	52-1/2 in x 5-15/16 in x 6-7/8 in
Weight	12.9 kg / 28.5 lb each
Finishes	Polished Aluminum, Black Chrome