



Millenia™ ADP

Design	5-driver, 3-way acoustic suspension, cast-aluminum / ABS enclosure, surround / rear
Crossover	1st-order electro-acoustic at 2.0 kHz, 2nd-order electro-acoustic at 300 Hz (bass driver)
High-Frequency Driver	Two 25-mm (1 in) S-PAL™ domes, die-cast chassis, ferro-fluid cooled
Midrange Driver(s)	Two 102-mm (4 in) MLP™ cones, 38-mm (1-1/2 in) dual-layer voice coils, HTD™ system die-cast heatsink chassis
Bass Driver	150-mm (6 in) mineral-filled polypropylene cone, 38-mm (1-1/2 in) dual-layer voice coils, HTD™ system die-cast heatsink chassis
Low Frequency Extension	62 Hz (DIN)
Frequency Response:	
On-Axis	±2 dB from 95 Hz - 20 kHz (reverberant soundfield)
30° Off-Axis	±
Sensitivity - Room / Anechoic	88 dB / 85 dB
Suitable Amplifier Power Range	15 - 200 watts
Maximum Input Power	100 watts
Impedance	Compatible with 8 ohms
Internal Volume	5.6 L / 0.20 cu ft
Height, Width, Depth	12.7 cm x 30.4 cm x 17.6 cm

	5 in x 11-15/16 in x 6-15/16 in
Weight	5.9 kg / 13 lb each
Finishes	Black, White