



SA-10R

Design	2-driver, 2-way in-ceiling / in-wall, GRIP™ chassis / mounting bracket
Crossover	3rd-order electro-acoustic at 2.5 kHz
High-Frequency Driver	25-mm (1 in) G-PAL™ dome, die-cast heatsink chassis, ferro-fluid cooled
Bass/Midrange Driver(s)	165-mm (6-1/2 in) S-PAL™ cone, 38-mm (1-1/2 in) voice coil, GRIP™ chassis
Low Frequency Extension	40 Hz (DIN)
Frequency Rresponse on axis	±2 dB from 60 Hz - 22 kHz
Frequency Rresponse 30 off axis	±2 dB from 60 Hz - 20 kHz
Sensitivity-Room/Anechoic	91 dB / 87 dB
Suitable Amplifier Power Range	150 - 15 watts
Maximum Input Power	90 watts
Impedance	Compatible with 8 ohms
Height,Width or Diameter	19.6 cm / 7-11/16 in (Diameter)
Minimum Mounting Depth	8.7 cm /3-7/16 in
Cutout Dimensions Diameter	17.2
Minimum Internal Volume Required	12 L / 0.4 cu ft
Pre-Installation Brackets	PB-7R
Weight	8lb / 3.60kg

