



## SA-15R-SM

Design	Single speaker system with Stereo L/R inputs, 2 x 2-way in-ceiling / in-wall, 3-driver, GRIP™ chassis / mounting bracket
Crossover	3rd-order electro-acoustic at 2.5 kHz
High-Frequency Driver	Two 25-mm (1 in) G-PAL™ domes, die-cast heatsink chassis, ferro-fluid cooled
Bass/Midrange Driver(s)	210-mm (8 in) S-PAL™ cone, Dual 38-mm (1-1/2 in) voice coils, GRIP™ chassis
Low Frequency Extension	37 Hz (DIN)
Frequency Rresponse on axis	±2 dB from 58 Hz - 22 kHz
Frequency Rresponse 30 off axis	±2 dB from 58 Hz - 17 kHz
Sensitivity-Room/Anechoic	92 dB / 88 dB
Suitable Amplifier Power Range	160 - 15 watts
Maximum Input Power	100 watts
Impedance	Compatible with 4 ohms Mono   Compatible with 8 ohms / channel Stereo
Height,Width or Diameter	22.6 cm / 8-7/8 in (Diameter)
Minimum Mounting Depth	9 cm /3-9/16 in
Cutout Dimensions Diameter	20
Minimum Internal Volume Required	20 L / 0.7 cu ft

Pre-Installation Brackets	PB -8R
Weight	11lb / 5.00kg
Finishes	White, paintable