



SA-30

Design	2-driver, 2-way in-wall / in-ceiling, die-cast chassis / mounting bracket
Crossover	3rd-order electro-acoustic at 2.0 kHz
High-Frequency Driver	25-mm (1 in) G-PAL™ dome, die-cast heatsink, ferro-fluid cooled
Bass/Midrange Driver(s)	210-mm (8 in) S-PAL™ cone, 38-mm (1-1/2 in) voice coil, die-cast chassis
Low Frequency Extension	35 Hz (DIN)
Frequency Rresponse on axis	±2 dB from 48 Hz - 22 kHz
Frequency Rresponse 30 off axis	±2 dB from 48 Hz - 20 kHz
Sensitivity-Room/Anechoic	93 dB / 89 dB
Suitable Amplifier Power Range	180 - 15 watts
Maximum Input Power	120 watts
Impedance	Compatible with 8 ohms
Height,Width or Diameter	31.4 cm x22.7 cm / 12-3/8 in x8-15/16 in (Height x Width)
Minimum Mounting Depth	7.4 cm /2-15/16 in
Cutout Dimensions	
Height x Width	11-9/16 in x 8-1/8 in (Height x Width)
Minimum Internal Volume Required	20 L / 0.7 cu ft

Pre-Installation Brackets	PB-8x12
Weight	16.7lb / 7.60kg
Finishes	White, paintable