



SA-LCR 3

Design	4-driver, 3-way in-wall left / center / right, critical bracing and volume supplied by required Paradigm® BX-LCR 3 backbox (sold separately)
Crossover	3rd-order electro-acoustic at 2.5 kHz, 2nd-order electro-acoustic at 450 Hz
High-Frequency Driver	25-mm (1 in) G-PAL™ dome, die-cast heatsink chassis, ferro-fluid cooled, IMS / SHOCK-MOUNT™
Bass Driver	die-cast chassis with AVS™ Airflow Ventilation System cooling, Two 178-mm (7 in) mineral-filled polypropylene cones, 38-mm (1-1/2 in) dual-layer voice coils, IMS / SHOCK-MOUNT™
Midrange Driver	die-cast chassis with AVS™ Airflow Ventilation System cooling, 25-mm (1 in) dual-layer voice coil, 115-mm (4-1/2 in) S-PAL™ cone, ferro-fluid cooled, IMS / SHOCK-MOUNT™
Low Frequency Extension	42 Hz (DIN)
Frequency Response on axis	±2 dB from 60 Hz - 22 kHz
Frequency Response 30 off axis	±2 dB from 60 Hz - 20 kHz
Sensitivity-Room/Anechoic	93 dB / 89 dB
Suitable Amplifier Power Range	15 - 200 watts
Maximum Input Power	150 watts
Impedance	Compatible with 8 ohms

Height,Width or Diameter	57.7 cm x23 cm / 22-11/16 in x9-1/16 in (Height x Width)
Weight	15lb / 6.80kg
Finishes	White, paintable
Backbox, required (sold separately)	BX-LCR 3
Backbox Dimensions: (H x W x D)	44 in in x 13-1/2 in in x 3-3/8 in in
	111.8 cm x 34.3 cm x 8.6 cm
Backbox Weight (unpacked)	20 lb / 9.1 kg each