



Signature ADP1 (P-Be™)

Design	3-way ultra-compact surround / rear on-wall, 5-driver
Crossover	2nd-order electro-acoustic at 300 Hz, 3rd-order electro-acoustic at 2.0 kHz
High-Frequency Driver	dual super-neodymium ring magnets, Two 25-mm (1 in) P-Be™ pure-beryllium domes, rear damping chambers with ARB™ aperiodic resonance breakup fins and integrated heatsink, die-cast heatsink chassis, ferro-fluid cooled, IMS / SHOCK-MOUNT™
Midrange Driver(s)	25-mm (1 in) dual-layer voice coils, super-neodymium ring magnets, Two 85-mm (3-1/2 in) Co-PAL™ cobalt-infused pure-aluminum cones, ATC™ asymmetric tapered dual-channel die-cast aluminum chambers, ferro-fluid cooled, AVS™ die-cast heatsink chassis, IMS / SHOCK-MOUNT™
Bass Driver	massive hard ferrite magnets, 38-mm (1-1/2 in) dual-layer long-excursion voice coil, overmolded NLC™ surrounds, integrated AVS™ baffle / die-cast heatsink chassis, 155-mm (6 in) mineral-filled polypropylene cone, IMS / SHOCK-MOUNT™
Low Frequency Extension	60 Hz (DIN)
Frequency Response:	

On-Axis	±2 dB from 100 Hz - 45 kHz (optimized reverberant soundfield)
30° Off-Axis	±
Sensitivity - Room / Anechoic	88 dB / 85 dB
Suitable Amplifier Power Range	15 - 225 watts
Maximum Input Power	140 watts
Impedance	Compatible with 8 ohms
Height, Width, Depth (Height includes spikes or outrigger feet)	19 cm x 30.5 cm x 15.5 cm 7-1/2 in x 12 in x 6-1/8 in
Weight	7.0 kg / 15.5 lb each
Finishes	Cherry, Natural Maple, Piano Black
Paradigm® Stand (sold sep.)	Paradigm® GS-30 in Bronze