



## Signature ADP1

Design	5-driver, 3-way surround / rear, optimized reverberant soundfield, on-wall
Crossover	2nd-order electro-acoustic at 300 Hz, 3rd-order electro-acoustic at 1.9 kHz
High-Frequency Driver	Two 25-mm (1 in) P-Be™ pure-beryllium domes, rear damping chambers with ARB™ aperiodic resonance breakup fins and integrated heatsink, dual super neodymium magnets, die-cast heatsink chassis, ferro-fluid cooled, IMS / SHOCK-MOUNT™
Midrange Driver(s)	dual super neodymium magnets, Two 85-mm (3-1/2 in) Co-PAL™ cobalt-infused pure-aluminum cones, solid aluminum phase plugs, dual-layer 25-mm (1 in) rigid, low-mass voice coils, ATC™ asymmetric tapered dual-channel die-cast aluminum chambers, AVS™ die-cast heatsink chassis, IMS / SHOCK-MOUNT™
Bass Driver	integrated AVS™ baffle / die-cast heatsink chassis, 155-mm (6 in) mineral-filled polypropylene cone, four-layer 38-mm (1-1/2 in) rigid, low-mass voice coil, IMS / SHOCK-MOUNT™
Low Frequency Extension	70 Hz (DIN)
Frequency Response:	
On-Axis	±2 dB from 99 Hz - 45 kHz

30° Off-Axis	±(optimized reverberant soundfield)
Sensitivity - Room / Anechoic	88 dB / 85 dB
Suitable Amplifier Power Range	15 - 225 watts
Maximum Input Power	140 watts
Impedance	Compatible with 8 ohms
Internal Volume	5.6 L / 0.2 cu ft
Height, Width, Depth	19 cm x 30.5 cm x 15.5 cm
(Height includes spikes or outrigger feet)	7-1/2 in x 12 in x 6-1/8 in
Weight	14.1 kg / 31 lb per pair
Finishes	Cherry, Natural Birdseye Maple, Piano Black
Matching Speaker Stand	GS-30