



Signature C1 (P-Be™)

Design	3-way ultra-compact center channel, 4-driver
Crossover	2nd-order electro-acoustic at 550 Hz (bass drivers), 3rd-order electro-acoustic at 2.3 kHz
High-Frequency Driver	dual super-neodymium ring magnets, die-cast enclosure / integrated heatsink chassis, 25-mm (1 in) P-Be™ pure-beryllium dome, rear damping chamber with ARB™ aperiodic resonance breakup fins and integrated heatsink, ferro-fluid cooled
Midrange Driver(s)	85-mm (3-1/2 in) Co-PAL™ cobalt-infused pure-aluminum cone, 25-mm (1 in) dual-layer voice coil, ATC™ asymmetric tapered dual-channel die-cast aluminum chamber, dual super-neodymium ring magnets, ferro-fluid cooled, AVS™ die-cast heatsink chassis
Bass Driver	super-neodymium ring magnets, 38-mm (1-1/2 in) two-layer split voice coils, overmolded NLC™ surrounds, Two 127-mm (5 in) mineral-filled polypropylene cones, AVS™ die-cast heatsink chassis
Low Frequency Extension	58 Hz (DIN)
Frequency Response:	
On-Axis	±2 dB from 73 Hz - 35 kHz
30° Off-Axis	±2 dB from 73 Hz - 20 kHz

Sensitivity - Room / Anechoic	88 dB / 85 dB
Suitable Amplifier Power Range	15 - 225 watts
Maximum Input Power	140 watts
Impedance	Compatible with 8 ohms
Height, Width, Depth (Height includes spikes or outrigger feet)	18 cm x 43 cm x 22.5 cm 7-1/16 in x 16-15/16 in x 8-7/8 in
Weight	11.3 kg / 25 lb each
Finishes	Cherry, Natural Maple, Piano Black