



Signature C3

Design	4-driver, 3-way center channel, MagneShield™††
Crossover	3rd-order electro-acoustic at 1.9 kHz, 2nd-order electro-acoustic at 250 Hz
High-Frequency Driver	25-mm (1 in) P-Be™ pure-beryllium dome, rear damping chamber with ARB™ aperiodic resonance breakup fins and integrated heatsink, dual super neodymium magnets, die-cast heatsink chassis, ferro-fluid cooled, IMS / SHOCK-MOUNT™
Midrange Driver(s)	102-mm (4 in) Co-PAL™ cobalt-infused pure-aluminum cone, solid aluminum phase plug, dual-layer 25-mm (1 in) rigid, low-mass voice coil, ATC™ asymmetric tapered dual-channel die-cast aluminum chamber, massive ceramic / ferrite magnets, AVS™ die-cast heatsink chassis, IMS / SHOCK-MOUNT™
Bass Driver	Two 178-mm (7 in) mineral-filled polypropylene cones, dual-layer 38-mm (1-1/2 in) rigid, low-mass voice coils, AVS™ die-cast heatsink chassis, IMS / SHOCK-MOUNT™
Low Frequency Extension	32 Hz (DIN)
Frequency Response:	
On-Axis	±2 dB from 55 Hz - 45 kHz
30° Off-Axis	±2 dB from 55 Hz - 20 kHz

Sensitivity - Room / Anechoic	91 dB / 88 dB
Suitable Amplifier Power Range	15 - 325 watts
Maximum Input Power	180 watts
Impedance	Compatible with 8 ohms
Internal Volume	23.9 L / 0.84 cu ft
Height, Width, Depth	24.1 cm x 67.3 cm x 33 cm
(Height includes spikes or outrigger feet)	9-1/2 in x 26-1/2 in x 13 in
Weight	20.4 kg / 45 lb each
Finishes	Cherry, Natural Birdseye Maple, Piano Black
Matching Speaker Stand	Paradigm® J-18C