



## Signature S1 (P-Be™)

Design	2-way ultra-compact bookshelf / stand-mounted, 2-driver
Crossover	3rd-order electro-acoustic at 2.1 kHz
High-Frequency Driver	dual super-neodymium ring magnets, die-cast enclosure / integrated heatsink chassis, 25-mm (1 in) P-Be™ pure-beryllium dome, rear damping chamber with ARB™ aperiodic resonance breakup fins and integrated heatsink, ferro-fluid cooled
Bass / Midrange Driver(s)	super-neodymium ring magnet, 38-mm (1-1/2 in) split voice coil, overmolded NLC™ surround, integrated AVS™ baffle / die-cast heatsink chassis, 155-mm (6 in) Co-PAL™ cobalt-infused pure-aluminum cone
Low Frequency Extension	43 Hz (DIN)
Frequency Response:	
On-Axis	±2 dB from 65 Hz - 45 kHz
30° Off-Axis	±2 dB from 65 Hz - 20 kHz
Sensitivity - Room / Anechoic	90 dB / 87 dB
Suitable Amplifier Power Range	15 - 175 watts
Maximum Input Power	100 watts
Impedance	Compatible with 8 ohms
Height, Width, Depth	27 cm x 17 cm x 22 cm
(Height includes spikes or outrigger feet)	10-5/8 in x 6-11/16 in x 8-11/16 in

Weight	5.7 kg / 12.5 lb each
Finishes	Cherry, Natural Maple, Piano Black
Paradigm® Stand (sold sep.)	Paradigm® GS-30 in Bronze