



Signature S8

Design	6-driver, 3-way floorstanding, MagneShield™††
Crossover	3rd-order electro-acoustic at 1.9 kHz, 2nd-order electro-acoustic at 250 Hz (lower bass drivers)
High-Frequency Driver	25-mm (1 in) P-Be™ pure-beryllium dome, rear damping chamber with ARB™ aperiodic resonance breakup fins and integrated heatsink, dual super neodymium magnets, die-cast heatsink chassis, ferro-fluid cooled, IMS / SHOCK-MOUNT™
Midrange Driver(s)	178-mm (7 in) Co-PAL™ cobalt-infused pure-aluminum cone, solid aluminum phase plug, two-layer 38-mm (1-1/2 in) rigid, low-mass voice coil, ATC™ asymmetric tapered dual-channel die-cast aluminum chamber, super neodymium magnets, ferro-fluid cooled, AVS™ die-cast heatsink chassis, IMS / SHOCK-MOUNT™
Bass Driver	Four 178-mm (7 in) mineral-filled polypropylene cones, four-layer 38-mm (1-1/2 in) rigid, low-mass voice coils, AVS™ die-cast heatsink chassis, massive ceramic / ferrite magnets, IMS / SHOCK-MOUNT™
Low Frequency Extension	26 Hz (DIN)
Frequency Response:	
On-Axis	±2 dB from 42 Hz - 45 kHz
30° Off-Axis	±2 dB from 42 Hz - 20 kHz

Sensitivity - Room / Anechoic	92 dB / 89 dB
Suitable Amplifier Power Range	15 - 500 watts
Maximum Input Power	250 watts
Impedance	Compatible with 8 ohms
Internal Volume	74.9 L / 2.6 cu ft
Height, Width, Depth	123.2 cm x 21 cm x 52.1 cm
(Height includes spikes or outrigger feet)	48-1/2 in x 8-1/4 in x 20-1/2 in
Weight	90.7 kg / 200 lb per pair
Finishes	Cherry, Natural Birdseye Maple, Piano Black