



Signature W5 C

Design	3-way center channel, on-wall / shelf-mounting, 6-driver
Crossover	2nd-order electro-acoustic at 300 Hz, 3rd-order electro-acoustic at 2.0 kHz
High-Frequency Driver	25-mm (1 in) P-Be™ pure-beryllium dome, dual super neodymium magnets, die-cast heatsink chassis, ferro-fluid cooled, IMS / SHOCK-MOUNT™
Bass / Midrange Driver(s)	ceramic magnets, oversize ceramic magnets, 38-mm (1-1/2 in) voice coils, Two 178-mm (7 in) Co-PAL™ cones, AVS™ die-cast heatsink chassis, IMS / SHOCK-MOUNT™
Midrange Driver(s)	115-mm (4-1/2 in) Co-PAL™ cone, super neodymium magnet, solid aluminum phase plug, 25-mm (1 in) voice coil, ferro-fluid cooled, AVS™ die-cast heatsink chassis, IMS / SHOCK-MOUNT™
Bass Driver	oversize ceramic magnets, Two 178-mm (7 in) mineral-filled polypropylene cones, 38-mm (1-1/2 in) voice coils, AVS™ die-cast heatsink chassis, IMS / SHOCK-MOUNT™
Low Frequency Extension	44 Hz (DIN)
Frequency Response:	
On-Axis	±2 dB from 70 Hz - 45 kHz
30° Off-Axis	±2 dB from 70 Hz - 20 kHz

Sensitivity - Room / Anechoic	94 dB / 90 dB
Suitable Amplifier Power Range	15 - 450 watts
Maximum Input Power	225 watts
Impedance	compatible with 8 ohms
Height, Width, Depth	22.7 cm x 95 cm x 14.3 cm
(Height includes spikes or outrigger feet)	8-15/16 in x 37-3/8 in x 5-5/8 in
Weight	17.7 kg / 39 lb each
Finishes	Cherry, Natural Birdseye Maple, Piano Black