



ART EMBRACING SCIENCE™



Studio 20

Design	2-driver, 2-way bookshelf / stand-mounted
Crossover	2nd-order electro-acoustic at 2.0 kHz
High-Frequency Driver	25-mm (1 in) G-PAL™ dome, die-cast heatsink chassis, ferro-fluid cooled, IMS / SHOCK-MOUNT™
Bass / Midrange Driver(s)	178-mm (7 in) S-PAL™ cone, 38-mm (1-1/2 in) voice coil, AVS™ die-cast heatsink chassis, IMS / SHOCK-MOUNT™
Low Frequency Extension	36 Hz (DIN)
Frequency Response:	
On-Axis	±2 dB from 54 Hz - 22 kHz
30° Off-Axis	±2 dB from 54 Hz - 20 kHz
Sensitivity - Room / Anechoic	90 / 87 dB
Suitable Amplifier Power Range	15 - 150 watts
Maximum Input Power	100 watts
Impedance	Compatible with 8 ohms
Internal Volume	15 L / 0.5 cu ft
Height, Width, Depth	38.1 cm x 21 cm x 32.3 cm
(Height includes spikes or outrigger feet)	15 in x 8-1/4 in x 12-11/16 in
Weight	19.5 kg / 43 lb per pair
Finishes	Rosenut, Black Ash, Cherry
Matching Speaker Stand	J-26, J-29