



Studio 40

Design	3-driver, 2-1/2-way bookshelf / stand-mounted
Crossover	2nd-order electro-acoustic at 2.0 kHz, 2nd-order electro-acoustic at 500 Hz (lower bass driver)
High-Frequency Driver	25-mm (1 in) G-PAL™ dome, die-cast heatsink chassis, ferro-fluid cooled, IMS / SHOCK-MOUNT™
Bass / Midrange Driver(s)	178-mm (7 in) S-PAL™ cone, 38-mm (1-1/2 in) voice coil, AVS™ die-cast heatsink chassis, IMS / SHOCK-MOUNT™
Bass Driver	178-mm (7 in) mineral-filled polypropylene cone, 38-mm (1-1/2 in) voice coil, AVS™ die-cast heatsink chassis, IMS / SHOCK-MOUNT™
Low Frequency Extension	36 Hz (DIN)
Frequency Response:	
On-Axis	±2 db from 62 Hz — 22 kHz
30° Off-Axis	±2 db from 62 Hz — 20 kHz
Sensitivity - Room / Anechoic	92 / 89 dB
Suitable Amplifier Power Range	15 - 180 watts
Maximum Input Power	140 watts
Impedance	Compatible with 8 ohms
Internal Volume	23 L / 0.8 cu ft
Height, Width, Depth	55.9 cm x 21 cm x 32.3 cm

(Height includes spikes or outrigger feet)	22 in x 8-1/4 in x 12-11/16 in
Weight	31.8 kg / 70 lb per pair
Finishes	Rosenut, Black Ash, Cherry
Matching Speaker Stand	J-23, J-26