



## Studio CC-490

Design	4-driver, 3-way center channel
Crossover	2nd-order electro-acoustic at 500 Hz (bass drivers), 2nd-order electro-acoustic at 2.1 kHz
High-Frequency Driver	25-mm (1 in) G-PAL™ dome, die-cast heatsink chassis, ferro-fluid cooled, IMS / SHOCK-MOUNT™
Midrange Driver(s)	89-mm (3-1/2 in) S-PAL™ cone, 25-mm (1 in) voice coil, ferro-fluid cooled, AVS™ die-cast heatsink chassis, IMS / SHOCK-MOUNT™
Bass Driver	Two 140-mm (5-1/2 in) mineral-filled polypropylene cones, 38-mm (1-1/2 in) voice coils, AVS™ die-cast heatsink chassis, IMS / SHOCK-MOUNT™
Low Frequency Extension	43 Hz (DIN)
Frequency Response:	
On-Axis	±2 dB from 65 Hz - 20 kHz
30° Off-Axis	±2 dB from 65 Hz - 18 kHz
Sensitivity - Room / Anechoic	90 dB / 87 dB
Suitable Amplifier Power Range	15 - 200 watts
Maximum Input Power	150 watts
Impedance	Compatible with 8 ohms
Height, Width, Depth (Height includes spikes or outrigger feet)	21.1 cm x 48.8 cm x 28.9 cm 8-5/16 in x 19-3/16 in x 11-3/8 in

Weight	12.2 kg / 27 lb each
Finishes	Cherry, Rosenut, Black