



Studio Esprit C

Design	4-driver, on-wall / shelf-mounted, 3-way center channel with ABEC™††
Crossover	3rd-order electro-acoustic at 550 Hz, 3rd-order electro-acoustic at 2.5 kHz
High-Frequency Driver	25-mm (1 in) G-PAL™ dome, die-cast heatsink chassis, ferro-fluid cooled, IMS / SHOCK-MOUNT™
Midrange Driver(s)	115-mm (4-1/2 in) S-PAL™ cone, 25-mm (1 in) voice coil, ferro-fluid cooled, AVS™ die-cast heatsink chassis, IMS / SHOCK-MOUNT™
Bass Driver	Two 178-mm (7 in) mineral-filled polypropylene cones, 38-mm (1-1/2 in) voice coils, AVS™ die-cast heatsink chassis, IMS / SHOCK-MOUNT™
Low Frequency Extension	46 Hz (DIN)
Frequency Response:	
On-Axis	±2 dB from 75 Hz - 20 kHz
30° Off-Axis	±2 dB from 75 Hz - 18 kHz
Sensitivity - Room / Anechoic	92 dB / 88 dB
Suitable Amplifier Power Range	15 - 200 watts
Maximum Input Power	150 watts
Impedance	Compatible with 8 ohms
Internal Volume	7.6 L / 0.27 cu ft
Height, Width, Depth	22.7 cm x 67 cm x 14.9 cm

(Height includes spikes or outrigger feet)	8-15/16 in x 26-3/8 in x 5-7/8 in
Weight	10.9 kg / 24 lb each
Finishes	High-Gloss Black, Cherry, Rosenut